















SPECIFICATIONS

	GEOLOGY	Sandstone
	TYPE	100% Bedface
	PATTERN	2:1 Natural Coursed Ashlar Random Ashlar
	HEIGHTS	3"-12" (Thin Veneer)
	LENGTHS	Thin Veneer Only: 6" - 20" (Crated or Palletized Material can exceed 20")
	DEPTHS	3/4" to 1-1/4" (Thin Veneer)
	COLORS	Gray-Grey
	COVERAGE	
	WEIGHT	12 lbs. per square foot.
	FLATS	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	CORNERS	10 In/ft Box, 100 In/ft Crate
	NOTES	

ASTM C-97

Water Absorption %	.12
Bulk Specific Gravity	2.78

ASTM C-170

Parallel to Rift, Dry (psi)	14214
Parallel to Rift, Wet (psi)	14213
Perpendicular to Rift, Dry (psi)	21814
Perpendicular to Rift, Wet (psi)	21320

ASTM C-99

Parallel to Rift, Dry (psi)	3046
Parallel to Rift, Wet (psi)	3191

ASTM C-880

Perpendicular to Rift, Dry (psi)	4351
Perpendicular to Rift, Wet (psi)	4351