















**SPECIFICATIONS**

	<b>GEOLOGY</b>	Sandstone
	<b>TYPE</b>	100% Bedface
	<b>PATTERN</b>	2:1 Natural Coursed Ashlar   Random Ashlar
	<b>HEIGHTS</b>	3"-12" (Thin Veneer)
	<b>LENGTHS</b>	Thin Veneer Only: 6" - 20" (Crated or Palletized Material can exceed 20")
	<b>DEPTHS</b>	3/4" to 1-1/4" (Thin Veneer)
	<b>COLORS</b>	Gray-Grey
	<b>COVERAGE</b>	
	<b>WEIGHT</b>	12 lbs. per square foot.
	<b>FLATS</b>	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	<b>CORNERS</b>	10 In/ft Box, 100 In/ft Crate
	<b>NOTES</b>	

**ASTM C-97**

Water Absorption %	.12
Bulk Specific Gravity	2.78

**ASTM C-170**

Parallel to Rift, Dry (psi)	14214
Parallel to Rift, Wet (psi)	14213
Perpendicular to Rift, Dry (psi)	21814
Perpendicular to Rift, Wet (psi)	21320

**ASTM C-99**

Parallel to Rift, Dry (psi)	3046
Parallel to Rift, Wet (psi)	3191

**ASTM C-880**

Perpendicular to Rift, Dry (psi)	4351
Perpendicular to Rift, Wet (psi)	4351

