Fond du Lac Natural stone
BUILDING & LANDSCAPE STONE

ENVISION
REAL Stone. REAL Texture.
SEE it on your REAL Home.

Summit™



SPECIFICATIONS

GEOLOGY	Sandstone
TYPE	Tumbled, 100% Bedface
PATTERN	Natural Coursed Ashlar | 2:1 Random Ashalr
HEIGHTS	4"-12" (Thin Veneer)
LENGTHS	6"-20" (Thin Veneer, crated material may exceed 20")
DEPTHS	3/4" to 1-1/4" (Thin Veneer)
COLORS	Browns, possible plum, Gray-Grey
COVERAGE	
WEIGHT	12.6 lbs. per square foot.
FLATS	10 s/f Box, 100 s/f Crate, 180 s/f Crate
CORNERS	10 l/f Box, 100 l/f Crate, Crated material can exceed 20"
NOTES	Tumbled version of Warwick; 30% Camelback – 70% Grays

ASTM C-97

Water Absorption %	1.2
Bulk Specific Gravity	2.53

ASTM C-170

Parallel to Rift, Dry (psi)	29300
Parallel to Rift, Wet (psi)	
Perpendicular to Rift, Dry (psi)	19200
Perpendicular to Rift, Wet (psi)	14150

ASTM C-99

Parallel to Rift, Dry (psi)	3225
Parallel to Rift, Wet (psi)	2495

ASTM C-880

Perpendicular to Rift, Dry (psi)	931
Perpendicular to Rift, Wet (psi)	911

Fond du Lac Natural Stone | fdlnaturalstone.com
N4224 Hwy 175 PO Box 347 Fond du Lac, WI 54936-0347
Phone: 920-923-2800 | Toll Free: 877-923-2800 | Fax: 920-923-3800