



SPECIFICATIONS

	GEOLOGY	100% Splitface
	TYPE	Limestone
	PATTERN	Natural Course Heights 2:1 Random Ashlar
	HEIGHTS	2 in - 9 in
	LENGTHS	8 in - 20 in (Crated or palletized material up to 36")
	DEPTHS	Thin Veneer: .75 in - 1.25 in Full Veneer: 3 in - 5 in
	COLORS	Light to medium gray, buff, tan
	COVERAGE	35 - 40 square feet per ton (Full Veneer)
	WEIGHT	14.9 lbs. per square foot (Thin Veneer)
	FLATS	10 s/f Box, 100 s/f Crate or Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	10 l/f Box; 100 l/f Crate or Pallet
	NOTES	Pre-packaged blend of 50% Fond du Lac Country and 50% Tundra Country . (Shown with SpecMix "SM200-White" mortar joints)

ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730