

SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	100% Bedface
	PATTERN	2: Sawn Course Heights Dimensional Ashlar
	HEIGHTS	2.25", 5"
	LENGTHS	Thin Veneer: 6" - 20" (Crated or palletized material can exceed 20")
	DEPTHS	Thin Veneer: .75" - 1.25" Full Veneer: 3" - 5"
	COLORS	Muted beige, buff, grays
	COVERAGE	35 - 40 Sq Ft per Ton (Full Veneer)
	WEIGHT	~13.4 lbs per Sq Ft (Thin Veneer)
	FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 200 s/f Pallet
	CORNERS	Ln/Ft Box; 100 Ln/Ft Crate; 100 Ln/Ft Pallet
	NOTES	NEW (Tumbled version of " Albany ", which is Fond du Lac Dimensional with 2.25" & 5" heights only.)

ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730