



SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	Tumbled, 100% Bedface
	PATTERN	2:1 Dimensional Ashlar
	HEIGHTS	2-1/4" (20%), 5" (50%), 7-3/4" (30%): Thin and Full Veneer
	LENGTHS	Full Veneer: 8" - 48" Thin Veneer: 6" - 20" (Crated or Palletized material can exceed 20")
	DEPTHS	3/4" - 1 1/4" (Thin Veneer); 3"-5" Full Veneer
	COLORS	Gray, Buff, Tan
	COVERAGE	35-40 square feet per ton (full veneer)
	WEIGHT	13.4 lbs. per square foot (Thin Veneer)
	FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	10 l/f Box; 100 l/f Crate; 100 l/f pallet
	NOTES	NEW (Pre-packaged 50/50 blend of "Nashville" & "Lakewood")

ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730