















**SPECIFICATIONS**

	<b>GEOLOGY</b>	Sandstone
	<b>TYPE</b>	100% Splitface
	<b>PATTERN</b>	Coursed Dimensional Ashlar   2:1 Dimensional Ashlar
	<b>HEIGHTS</b>	2-1/4" (20%), 5" (50%), 7-3/4" (30%)
	<b>LENGTHS</b>	Thin Veneer: 8"-20"; Full Bed-Depth: 8" - 36"
	<b>DEPTHS</b>	Thin Veneer: 3/4" to 1-1/4"; Full Bed-Depth: 3" - 5"
	<b>COLORS</b>	Beige, Brown, Buff, Salmon, Tan
	<b>COVERAGE</b>	35-40 sf per ton (Full Bed-Depth)
	<b>WEIGHT</b>	12.3 lbs. per square foot (Thin Veneer)
	<b>FLATS</b>	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	<b>CORNERS</b>	10 l/f Box, 100 l/f Crate; Crated material can exceed 20"
	<b>NOTES</b>	

**ASTM C-97**

Water Absorption %	3.8
Bulk Specific Gravity	2.4

**ASTM C-170**

Parallel to Rift, Dry (psi)	4115
Parallel to Rift, Wet (psi)	2612
Perpendicular to Rift, Dry (psi)	
Perpendicular to Rift, Wet (psi)	

**ASTM C-99**

Parallel to Rift, Dry (psi)	1912
Parallel to Rift, Wet (psi)	2054

**ASTM C-880**

Perpendicular to Rift, Dry (psi)	670
Perpendicular to Rift, Wet (psi)	991

