















## SPECIFICATIONS

	<b>GEOLOGY</b>	Limestone
	<b>TYPE</b>	50% Splitface, 50% Sawntface
	<b>PATTERN</b>	1:1 (Coursed)
	<b>HEIGHTS</b>	2-1/2"
	<b>LENGTHS</b>	6" - 20" (Crated or palletized material can exceed 20")
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Cream to White
	<b>COVERAGE</b>	Not available in Full Veneer.
	<b>WEIGHT</b>	11
	<b>FLATS</b>	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	<b>CORNERS</b>	10 l/f Box, 100 l/f Crate
	<b>NOTES</b>	

### ASTM C-97

Water Absorption %
Bulk Specific Gravity

### ASTM C-170

Parallel to Rift, Dry (psi)
Parallel to Rift, Wet (psi)
Perpendicular to Rift, Dry (psi)
Perpendicular to Rift, Wet (psi)

### ASTM C-99

Parallel to Rift, Dry (psi)
Parallel to Rift, Wet (psi)

### ASTM C-880

Perpendicular to Rift, Dry (psi)
Perpendicular to Rift, Wet (psi)