















SPECIFICATIONS

| | | |
|--|-----------------|---|
|  | GEOLOGY | Sandstone |
|  | TYPE | 100% Bedface |
|  | PATTERN | 2:1 Dimensional Ashlar or Coursed |
|  | HEIGHTS | 2-1/2", 5" |
|  | LENGTHS | Thin Veneer Only: 6" - 20" (Crated or Palletized material can exceed 20") |
|  | DEPTHS | 3/4" to 1-1/4" |
|  | COLORS | Medium grays |
|  | COVERAGE | Available in thin veneer only. |
|  | WEIGHT | 12.5 lbs per square foot |
|  | FLATS | 10 s/f Box, 100 s/f Crate, 180 s/f Crate |
|  | CORNERS | 10 ln/ft Box, 100 ln/ft Crate |
|  | NOTES | Packaged assuming a tight-fit installation. |

ASTM C-97

| | |
|-----------------------|------|
| Water Absorption % | .12 |
| Bulk Specific Gravity | 2.78 |

ASTM C-170

| | |
|----------------------------------|-------|
| Parallel to Rift, Dry (psi) | 14214 |
| Parallel to Rift, Wet (psi) | 14213 |
| Perpendicular to Rift, Dry (psi) | 21814 |
| Perpendicular to Rift, Wet (psi) | 21320 |

ASTM C-99

| | |
|-----------------------------|------|
| Parallel to Rift, Dry (psi) | 3046 |
| Parallel to Rift, Wet (psi) | 3191 |

ASTM C-880

| | |
|----------------------------------|------|
| Perpendicular to Rift, Dry (psi) | 4351 |
| Perpendicular to Rift, Wet (psi) | 4351 |



GOLD QUARRIER
ANSI/NSC 373-2013
C0290908-101



GOLD FABRICATOR
ANSI/NSC 373-2013
C0289215-101