



SPECIFICATIONS

	GEOLOGY	60% Splitface, 40% Bedface
	TYPE	Limestone
	PATTERN	Natural Course Heights 2:1 Random Ashlar
	HEIGHTS	Random, 2 in - 12 in (Full Bed & Thin Veneer)
	LENGTHS	Full Bed: 8"-36" Thin Veneer: 6"-20" (Crated or palletized material can exceed 20")
	DEPTHS	Thin Veneer: .75" - 1.25" Full Veneer: 3" - 5"
	COLORS	Buff, light to medium grays
	COVERAGE	Full Veneer: 35-40 square feet per ton
	WEIGHT	14.9 lbs per sq ft
	FLATS	10 s/f Box, 100 s/f Crate, 180 s/f per Crate; 100 s/f Pallet, 200 s/f Pallet
	CORNERS	10 Ln/ft Box, 100 Ln/ft Crate; 100 Ln/ft Pallet
	NOTES	Pre-packaged blend of 60% Split face (Cavalier), 40% Bedface (Fond du Lac Manor)

ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730