















## SPECIFICATIONS

	<b>GEOLOGY</b>	Mica-Schist Quartz (Quartzitic Sandstone)
	<b>TYPE</b>	
	<b>PATTERN</b>	2:1 or 2:3, Sawn Course Heights   Dimensional   Tight-fit
	<b>HEIGHTS</b>	1" - 2" (~50%), 3" (~25%), 5" (~25%)
	<b>LENGTHS</b>	Thin Veneer Only: 6" - 20" (Crated or palletized material can exceed 20")
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Gray-Grey , Silver
	<b>COVERAGE</b>	Available in thin veneer only.
	<b>WEIGHT</b>	12.7 lbs. per square foot
	<b>FLATS</b>	5 s/f Bag, 10 s/f Box, 90/150/180 s/f Crate
	<b>CORNERS</b>	5 l/f Bag, 10 l/f Box, 90/100 l/f Crate
	<b>NOTES</b>	Packaged assuming a tight-fit installation comprising of 50% <b>Silver Ledgestone</b> , 50% sawn-height jumpers.   Please review the <b>Corners Installation</b> PDF document.

### ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

### ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

### ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

### ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730

