















SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	100% Bedface
	PATTERN	2:1 or Sawn Coursed Heights Dimensional Tight-fit
	HEIGHTS	2.5", 5"
	LENGTHS	Thin Veneer: 6" - 20" (Crated or Palletized Material can exceed 20")
	DEPTHS	3/4" - 1 1/4" (.75" - 1.25")
	COLORS	Beige , Buff , Gray-Grey
	COVERAGE	Available in thin veneer only.
	WEIGHT	13.7 lbs per square foot
	FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	10 l/f Box; 100 l/f Crate; 100 l/f Pallet
	NOTES	* Packaged assuming a tight-fit installation.

ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730