



SPECIFICATIONS

	GEOLOGY	Mica-Schist Quartz (quartzitic sandstone)
	TYPE	
	PATTERN	2:1 or 2:3, Sawn Course Heights Dimensional or Ashlar Tight-fit
	HEIGHTS	1" - 2" (~50%); 3" (~25%), 5" (~25%)
	LENGTHS	Thin Veneer Only: 6" - 20"
	DEPTHS	3/4" to 1-1/4"
	COLORS	Buff, Brown hues, Bronze, Copper, Gray-Grey, Silver
	COVERAGE	Available in thin veneer only.
	WEIGHT	12.7 lbs per square foot
	FLATS	5 s/f Bag, 10 s/f Box, 90/150/180 s/f Crate
	CORNERS	5 l/f Bag, 10 l/f Box, 90/100 l/f crate
	NOTES	Packaged assuming a tight-fit installation comprising of 50% <i>Virginia Ledgestone</i>, 50% sawn-height jumpers. Please review the Corners Installation PDF document.

ASTM C-97

Water Absorption %	.9
Bulk Specific Gravity	

ASTM C-170

Parallel to Rift, Dry (psi)	18175
Parallel to Rift, Wet (psi)	31470
Perpendicular to Rift, Dry (psi)	
Perpendicular to Rift, Wet (psi)	

ASTM C-99

Parallel to Rift, Dry (psi)	5584
Parallel to Rift, Wet (psi)	5502

ASTM C-880

Perpendicular to Rift, Dry (psi)	3984
Perpendicular to Rift, Wet (psi)	1064

