



## SPECIFICATIONS

	<b>GEOLOGY</b>	Sandstone
	<b>TYPE</b>	~85% Bedface, ~15% Splitface
	<b>PATTERN</b>	2:1 Dimensional Ashlar, or Coursed.
	<b>HEIGHTS</b>	2", 4"
	<b>LENGTHS</b>	4" - 10"
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Beige, Black, Brown, Buff, Charcoal, Gray-Grey, Tan
	<b>COVERAGE</b>	
	<b>WEIGHT</b>	12.4 lbs per square foot
	<b>FLATS</b>	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	<b>CORNERS</b>	10 l/f Box, 100 l/f Crate
	<b>NOTES</b>	Packaged assuming a tight-fit installation.

### ASTM C-97

Water Absorption %	2.7
Bulk Specific Gravity	2.33

### ASTM C-170

Parallel to Rift, Dry (psi)	12000
Parallel to Rift, Wet (psi)	
Perpendicular to Rift, Dry (psi)	17100
Perpendicular to Rift, Wet (psi)	

### ASTM C-99

Parallel to Rift, Dry (psi)	2939
Parallel to Rift, Wet (psi)	

### ASTM C-880

Perpendicular to Rift, Dry (psi)	2041
Perpendicular to Rift, Wet (psi)	

