















## SPECIFICATIONS

|  |                 |   |
|--|-----------------|---|
|  | <b>GEOLOGY</b>  | Sandstone   |
|  | <b>TYPE</b>     | ~85% Bedface, ~15% Splitface                        |
|  | <b>PATTERN</b>  | 2:1 Dimensional Ashlar, or Coursed.                 |
|  | <b>HEIGHTS</b>  | 2", 4"  |
|  | <b>LENGTHS</b>  | 4" - 10"  |
|  | <b>DEPTHS</b>   | 3/4" to 1-1/4"                                      |
|  | <b>COLORS</b>   | Beige, Black, Brown, Buff, Charcoal, Gray-Grey, Tan |
|  | <b>COVERAGE</b> |   |
|  | <b>WEIGHT</b>   | 12.4 lbs per square foot                            |
|  | <b>FLATS</b>    | 10 s/f Box, 100 s/f Crate, 180 s/f Crate            |
|  | <b>CORNERS</b>  | 10 l/f Box, 100 l/f Crate                           |
|  | <b>NOTES</b>    | Packaged assuming a tight-fit installation.         |

### ASTM C-97

|                       |      |
|-----------------------|------|
| Water Absorption %    | 2.7  |
| Bulk Specific Gravity | 2.33 |

### ASTM C-170

|                                  |       |
|----------------------------------|-------|
| Parallel to Rift, Dry (psi)      | 12000 |
| Parallel to Rift, Wet (psi)      |       |
| Perpendicular to Rift, Dry (psi) | 17100 |
| Perpendicular to Rift, Wet (psi) |       |

### ASTM C-99

|                             |      |
|-----------------------------|------|
| Parallel to Rift, Dry (psi) | 2939 |
| Parallel to Rift, Wet (psi) |      |

### ASTM C-880

|                                  |      |
|----------------------------------|------|
| Perpendicular to Rift, Dry (psi) | 2041 |
| Perpendicular to Rift, Wet (psi) |      |

