















**SPECIFICATIONS**

	<b>GEOLOGY</b>	Sandstone
	<b>TYPE</b>	
	<b>PATTERN</b>	Coursed, 1:1 ("brick" pattern)
	<b>HEIGHTS</b>	2 1/4" (2.25")
	<b>LENGTHS</b>	7 5/8" +/- 1/8" (7.625" +/- .125")
	<b>DEPTHS</b>	.5" - .375" (1/2" - 3/8")
	<b>COLORS</b>	Buff, cream to light gray
	<b>COVERAGE</b>	
	<b>WEIGHT</b>	8
	<b>FLATS</b>	14, 120, 240 square feet
	<b>CORNERS</b>	10, 110 linear feet
	<b>NOTES</b>	Natural stone "thin brick". Packaged assuming a standard 3/8" grout joint.

**ASTM C-97**

Water Absorption %
Bulk Specific Gravity

**ASTM C-170**

Parallel to Rift, Dry (psi)
Parallel to Rift, Wet (psi)
Perpendicular to Rift, Dry (psi)
Perpendicular to Rift, Wet (psi)

**ASTM C-99**

Parallel to Rift, Dry (psi)
Parallel to Rift, Wet (psi)

**ASTM C-880**

Perpendicular to Rift, Dry (psi)
Perpendicular to Rift, Wet (psi)

