















**SPECIFICATIONS**

	<b>GEOLOGY</b>	Limestone
	<b>TYPE</b>	Tumbled, 100% Bedface
	<b>PATTERN</b>	Mosaic
	<b>HEIGHTS</b>	Irregular shaped up to 16" across
	<b>LENGTHS</b>	Up to 16" across
	<b>DEPTHS</b>	3/4" - 1 1/4" (Thin Veneer); 3"-5" Full Veneer
	<b>COLORS</b>	Beige, Buff, Tan hues with soft, aged appearance.
	<b>COVERAGE</b>	35-40 sq ft per ton (full bed-depth)
	<b>WEIGHT</b>	13.7 lbs. per square foot (Thin Veneer)
	<b>FLATS</b>	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	<b>CORNERS</b>	10 l/f Box; 100 l/f Crate; 100 l/f pallet
	<b>NOTES</b>	

**ASTM C-97**

Water Absorption %	.50
Bulk Specific Gravity	2.79

**ASTM C-170**

Parallel to Rift, Dry (psi)	21300
Parallel to Rift, Wet (psi)	20300
Perpendicular to Rift, Dry (psi)	29400
Perpendicular to Rift, Wet (psi)	29100

**ASTM C-99**

Parallel to Rift, Dry (psi)	2040
Parallel to Rift, Wet (psi)	1690

**ASTM C-880**

Perpendicular to Rift, Dry (psi)	
Perpendicular to Rift, Wet (psi)	



**GOLD QUARRIER**  
ANSI/NSC 373-2013  
C0290908-101



**GOLD FABRICATOR**  
ANSI/NSC 373-2013  
C0289215-101