















SPECIFICATIONS

	GEOLOGY	Sandstone
	TYPE	70% Splitface, 30% Bedface
	PATTERN	2:1 Random Ashlar
	HEIGHTS	3" - 6"
	LENGTHS	Thin Veneer: 6" - 20" (Crated or Palletized Material can exceed 20")
	DEPTHS	3/4" to 1-1/4"
	COLORS	Brown, Gray-Grey, Tan
	COVERAGE	
	WEIGHT	11.4 lbs. per square foot.
	FLATS	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	CORNERS	10 l/f Box, 100 l/f Crate
	NOTES	

ASTM C-97

Water Absorption %
Bulk Specific Gravity

ASTM C-170

Parallel to Rift, Dry (psi)
Parallel to Rift, Wet (psi)
Perpendicular to Rift, Dry (psi)
Perpendicular to Rift, Wet (psi)

ASTM C-99

Parallel to Rift, Dry (psi)
Parallel to Rift, Wet (psi)

ASTM C-880

Perpendicular to Rift, Dry (psi)
Perpendicular to Rift, Wet (psi)



GOLD QUARRIER
ANSI/NSC 373-2013
C0290908-101



GOLD FABRICATOR
ANSI/NSC 373-2013
C0289215-101