















## SPECIFICATIONS

	<b>GEOLOGY</b>	Limestone
	<b>TYPE</b>	Tumbled, 100% Bedface
	<b>PATTERN</b>	2:1 Random Ashlar
	<b>HEIGHTS</b>	2" - 8"
	<b>LENGTHS</b>	Thin Veneer: 6" - 20" (Crated or Palletized Material can exceed 20")
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Buff, Gray-Grey, Lavender
	<b>COVERAGE</b>	
	<b>WEIGHT</b>	14.4 lbs. per square foot.
	<b>FLATS</b>	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	<b>CORNERS</b>	10 l/f Box, 100 l/f Crate
	<b>NOTES</b>	

### ASTM C-97

Water Absorption %  
Bulk Specific Gravity

### ASTM C-170

Parallel to Rift, Dry (psi)  
Parallel to Rift, Wet (psi)  
Perpendicular to Rift, Dry (psi)  
Perpendicular to Rift, Wet (psi)

### ASTM C-99

Parallel to Rift, Dry (psi)  
Parallel to Rift, Wet (psi)

### ASTM C-880

Perpendicular to Rift, Dry (psi)  
Perpendicular to Rift, Wet (psi)



**GOLD QUARRER**  
ANSI/NSC 373-2013  
C0290908-101



**GOLD FABRICATOR**  
ANSI/NSC 373-2013  
C0289215-101