















SPECIFICATIONS

	GEOLOGY	Sandstone
	TYPE	~85% Bedface, ~15% splitface
	PATTERN	2:1 random ashlar
	HEIGHTS	4"-6"
	LENGTHS	6" - 20" (Crated or palletized material can exceed 20")
	DEPTHS	3/4" to 1-1/4"
	COLORS	Beige, Black, Brown, Buff, Charcoal, Gray-Grey, Tan
	COVERAGE	
	WEIGHT	12 lbs per square foot
	FLATS	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	CORNERS	10 l/f Box, 100 l/f Crate
	NOTES	

ASTM C-97

Water Absorption %	2.7
Bulk Specific Gravity	2.33

ASTM C-170

Parallel to Rift, Dry (psi)	12000
Parallel to Rift, Wet (psi)	
Perpendicular to Rift, Dry (psi)	17100
Perpendicular to Rift, Wet (psi)	

ASTM C-99

Parallel to Rift, Dry (psi)	2041
Parallel to Rift, Wet (psi)	

ASTM C-880

Perpendicular to Rift, Dry (psi)	2041
Perpendicular to Rift, Wet (psi)	



GOLD QUARRIER
ANSI/NSC 573-2013
C0290908-101



GOLD FABRICATOR
ANSI/NSC 573-2013
C0289215-101