















**SPECIFICATIONS**

	<b>GEOLOGY</b>	Sandstone
	<b>TYPE</b>	100% Splitface
	<b>PATTERN</b>	2:1 Natural Coursed Ashlar   Random Ashlar
	<b>HEIGHTS</b>	Random, 2" - 8"
	<b>LENGTHS</b>	Thin Veneer: 6" - 20" (Crated or Palletized Material can exceed 20")
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Beige, Brown, Buff, Lavender, Salmon
	<b>COVERAGE</b>	
	<b>WEIGHT</b>	11 lbs. per square foot.
	<b>FLATS</b>	10 s/f Box, 100 s/f Crate
	<b>CORNERS</b>	10 l/f Box, 100 l/f Crate
	<b>NOTES</b>	

**ASTM C-97**

Water Absorption %	2.6
Bulk Specific Gravity	2.33

**ASTM C-170**

Parallel to Rift, Dry (psi)	3849
Parallel to Rift, Wet (psi)	3824
Perpendicular to Rift, Dry (psi)	
Perpendicular to Rift, Wet (psi)	

**ASTM C-99**

Parallel to Rift, Dry (psi)	2819
Parallel to Rift, Wet (psi)	2982

**ASTM C-880**

Perpendicular to Rift, Dry (psi)	1375
Perpendicular to Rift, Wet (psi)	856

